

DC POWER 600V RHH/RHW LSZH CABLE

List 3 – Class B Stranding, Cloth Jacketed, LSZH, 600V

Exclusively distributed by Jupiter Communications



The **RG Flex family** of telecommunications power products has been tested and approved by Telcordia and meets the functional performance requirements of GR-347 Issue 3, TPR.9212 and ATIS-0600017.2014. Telcordia affirms that L2, L3 and L4 power cables are suitable for use in all telecommunications facilities including central offices, remote terminal applications and outside plant remote cabinets that house electronics equipment.



RG Flex L3, 2/0 AWG

Size AWG or kcmil	Stranding Number/dia (Inch)	Conductor diameter (inches)	Insulation min. Thickness (mils)	Nominal insulation diameter (inches)	Nominal braid diameter (inches)	Max.d.c.res. @20°C (ohms/ mft.)	Approx. Weight lbs./mft.
14	7/.0242"	0.071	45	0.165	0.200	2.730	33
12	7/.0305"	.090	45	0.185	0.220	1.720	44
10	7/.0385"	0.114	45	0.210	0.250	1.080	59
8	7/0.486"	0.143	60	0.270	0.320	0.678	83
6	7/.0612"	0.180	60	0.305	0.355	0.427	118
4	7/.0772"	0.227	60	0.350	0.400	0.269	174
2	7/.0974"	0.286	60	0.410	0.460	0.169	259
1	19/0.065"	0.326	80	0.496	0.582	0.136	354
1/0	19/.0745"	0.365	80	0.530	0.610	0.106	415
2/0	19/.0837"	0.411	80	0.575	0.630	0.084	510
4/0	19/.1055"	0.517	80	0.680	0.735	0.052	775
350	37/.0973"	0.667	95	0.860	0.915	0.032	1264
500	37/.1162"	0.797	95	0.990	1.045	0.022	1758
750	61/.1109"	0.978	110	1.200	1.260	0.0148	2619

Parameter	Value
Operating Voltage	600V
Maximum Operating Temperature	90 °C dry & 75°C wet
Flame Test	VW-1 and FT4
Low Smoke Test	ST1
Halogen Free	IEC60754 IEC60332

Conductor

Type L3 DC power cable has a Class B annealed tinned copper flexible stranded conductor as per ASTM B-33 and B172. A mylar tape is applied over the conductor to facilitate easy stripping.

Insulation

Thermosetting low-smoke, lead-free and silicone-free non-halogenated insulation, rated 90°C.

Protective Layer

Natural cotton braided layer.

Packaging

The ends of all cables supplied shall be capped or taped to prevent the ingress of moisture during shipping or storage.

Testing

Physical and electrical testing in accordance with the requirements of UL Standard 44, Subject 509 and 758, and CSA Standard C22.2 No. 210.2 M90 as AWM.

Cable Sheath Markings

RG Flex L3 NON-HAL(UL) E477980 ___ AWG RHH/RHW 90C DRY AND 75C WET FT4-ST1 OR AWM 3578 105C 600V VW-1 – c(UL) AWM I B 105C 600V FT4-ST1 ----Meets IEC60754, IEC60332

Sequential footage markings shall be applied at two foot intervals on one side of the cable. Add "FOR CT USE" before "(AWM 3578)" on sizes 1/0 AWG and larger.

Certified by



Products are subject to manufacturer tolerances and availability.

1 • 2018/07 rev 1



www.jupitercommunications.net sales@jupitercommunications.net

2130 S. Douglas Dr., Building D, Chandler AZ 85286

P 855-699-5140 ▶ 480-699-5140 ▶ F 480-926-0835

DC POWER 600V RHH/RHW LSZH CABLE

List 3 – Class B Stranding, Cloth Jacketed, LSZH, 600V

Exclusively distributed by Jupiter Communications



Reference

Tested and Approved to meet or exceed the following standards:

- KS-24194 and 24194 Compliant
- Telcordia GR-347-CORE Compliant
- ATIS 0600017.2014 Compliant
- TPR.9212 Compliant
- UL Listed as Central Office Power Cable
- UL Listed Standard 44: Thermoset Insulated Type RHH/RHW/ST1
- UL Listed: For Tray Cable Use (1/0 & Larger)
- FT-4 Flame Test Compliant
- VW-1 Flame Test Compliant
- CSA AWM 1 B 105C
- Zero Halogen
- IEC 60754 and IEC 60332 Compliant
- RoHS / Reach Compliant

RG Flex L3 Telephone Power Cable 600 Volts Class B Stranding - Braided

Size	Jupiter P/N Gray	Jupiter P/N Green	Jupiter P/N Red	Jupiter P/N Blue	Jupiter P/N Black
14 STR	14AWG-L3GY	14AWG-L3GN	14AWG-L3RD	14AWG-L3BL	14AWG-L3BK
12 STR	12AWG-L3GY	12AWG-L3GN	12AWG-L3RD	12AWG-L3BL	12AWG-L3BK
10 STR	10AWG-L3GY	10AWG-L3GN	10AWG-L3RD	10AWG-L3BL	10AWG-L3BK
8 STR	8AWG-L3GY	8AWG-L3GN	8AWG-L3RD	8AWG-L3BL	8AWG-L3BK
6 STR	6AWG-L3GY	6AWG-L3GN	6AWG-L3RD	6AWG-L3BL	6AWG-L3BK
4 STR	4AWG-L3GY	4AWG-L3GN	4AWG-L3RD	4AWG-L3BL	4AWG-L3BK
2 STR	2AWG-L3GY	2AWG-L3GN	2AWG-L3RD	2AWG-L3BL	2AWG-L3BK
1 STR	1AWG-L3GY	1AWG-L3GN	1AWG-L3RD	1AWG-L3BL	1AWG-L3BK
1/0 STR	1/0-L3GY	1/0-L3GN	1/0-L3RD	1/0-L3BL	1/0-L3BK
2/0 STR	2/0-L3GY	2/0-L3GN	2/0-L3RD	2/0-L3BL	2/0-L3BK
4/0 STR	4/0-L3GY	4/0-L3GN	4/0-L3RD	4/0-L3BL	4/0-L3BK
350 STR	350MCM-L3GY	350MCM-L3GN	350MCM-L3RD	350MCM-L3BL	350MCM-L3BK
500 STR	500MCM-L3GY	500MCM-L3GN	500MCM-L3RD	500MCM-L3BL	500MCM-L3BK
750 STR	750MCM-L3GY	750MCM-L3GN	750MCM-L3RD	750MCM-L3BL	750MCM-L3BK

Tracer cable available upon request

Products are subject to manufacturer tolerances and availability.

2 • 2018/07 rev 1



www.jupitercommunications.net sales@jupitercommunications.net

2130 S. Douglas Dr., Building D, Chandler AZ 85286

P 855-699-5140 ▶ 480-699-5140 ▶ F 480-926-0835